



ETON DSP CONTROL CENTER INSTALL

WINDOWS Vista, 7, 8, 8.1 & 10, BETA Version

Please download the latest version of the ETON DSP CONTROL CENTER from our website www.etongmbh.com

Download the ZIP file and save it on your Windows computer.

System requirements: Computer with Windows Vista, 7, 8, 8.1 and 10 and a WiFi module/WLAN card.

- STEP 1:** Download the ZIP file and save them on your computer.
- STEP 2:** Unpack the ZIP file (Setup + Setup ETON) into a folder.
- STEP 3:** Start „Setup.exe“ and follow the Installation Wizard.
- STEP 4:** Select a storage location and select for whom the programme is to be installed.
- STEP 5:** Allow the installation routine to run in Windows.
- STEP 6:** Confirm the installation process with „close“.
- STEP 7:** After you have successfully completed the installation you can use both installation delete files.
- STEP 8:** Connect your computer to the ETON DSP power amplifier, open the WiFi/WLAN menu of your computer. Your amplifier is as a WiFi network listed, connect to this (scan the QR password from the amplifier on the back or on the product packaging).
- STEP 9:** Once you are connected to the amplifier, open the previously installed ETON DSP CONTROL CENTER.
- STEP 10:** The software now connects to your amplifier. Once you are connected a green tab „Connected“ at the top of the right page is displayed. If you are not connected, it says „disconnected“. In this case you can connect with a click on „disconnected“. A new Start connection process begins. A Pop-Up Dialog appears.
- STEP 11:** You can now configure your DSP amplifier. Please make sure that you are configured with the settings while you are connected „live“, i.e. you should always use the settings you have made. Save before closing the application. Otherwise, unsaved settings will be lost.

